


**Circular M12 Socket, A Coding, 5 Position,
Wire Leads, 4A, 60V, 22AWG, 0.1m**

**RoHS
Compliant**

Stock No.: 9223097M0046

FEATURES

- M12
- 5 Position
- Socket, Female
- Panel Mount



Product Description

























Circular connectors offer rugged solutions that have been engineered for reliable performance in a wide variety of harsh environmental applications, including aerospace, broadcast, defense and security, electronics, energy, industrial, instrumentation, medical, and transportation.





General Specifications

Attribute	Value
Standard	IEC 61076-2-101
Ambient temperature	-15°C ~ +85°C
Connector insert	PA
Connector contacts	Gold plated brass
Coupling nut/screw	Nickel plated Zinc Alloy
Seal/O-ring	Epoxy resin / FKM
Insulation resistance	≥100MΩ
Contact resistance	≤5mΩ
Shielding	-
Ingress Protection	IP67, IP68 in locked condition
Mating endurance	>500 cycles
Rated current	4A
Rated voltage	60V AC/DC
Wire gauge	0.34mm ² (AWG22)
Cable Length	0.1m

Product Drawing

Default Wire Color

Pin Number				
Pin 1	Brown 	Brown 	Brown 	White 
Pin 2		White 	White 	Brown 
Pin 3	Blue 	Blue 	Blue 	Green 
Pin 4	Black 	Black 	Black 	Yellow 
Pin 5			Gray 	Gray 
Pin 6				Pink 
Pin 7				Blue 
Pin 8				Red 

Contacts	3	4	6	8
Pin Layout (Female)				

Dimensions: Millimeters (Inches)

Part Number Table

Part Number	Description
9223747M0123	Circular M12 Socket, A Coding, 3 Position, Wire Leads, 4A, 250V, 22AWG, 0.1m
9223748M0124	Circular M12 Socket, A Coding, 3 Position, Wire Leads, 4A, 250V, 22AWG, 0.3m
9223749M0125	Circular M12 Socket, A Coding, 4 Position, Wire Leads, 4A, 250V, 22AWG, 0.1m
9223065M0014	Circular M12 Socket, A Coding, 4 Position, Wire Leads, 4A, 250V, 22AWG, 0.2m
9223750M0126	Circular M12 Socket, A Coding, 4 Position, Wire Leads, 4A, 250V, 22AWG, 0.3m
9223097M0046	Circular M12 Socket, A Coding, 5 Position, Wire Leads, 4A, 60V, 22AWG, 0.1m
9223090M0039	Circular M12 Socket, A Coding, 5 Position, Wire Leads, 4A, 60V, 22AWG, 0.3m
9223751M0127	Circular M12 Socket, A Coding, 8 Position, Wire Leads, 2A, 30V, 22AWG, 0.1m
9223752M0128	Circular M12 Socket, A Coding, 8 Position, Wire Leads, 2A, 30V, 22AWG, 0.3m

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate, but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.