



	XX	A
	10	1.0
	12	1.2
	15	1.5
	17	1.7
	20	2.0
	25	2.5



- SPECIFICATION:**
1. Insulation Resistance: Over 100MΩ at 500V DC.
 2. Dielectric strength: 2000V AC 1 Minute.
 3. Body Material: Thermoplastic 94V-2~V-0.
 4. Withdrawing force : 10N~50N.

Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	ENEC
	CCC
Rating:AC 15A 250V	
Mark	Safety Regulation
	CULUS

R 富灣股份有限公司
 RICH BAY COMPANY LTD.
 台北縣樹林市東興街57號
 NO. 57, Tung Hsing St., Shu-Lin Town,
 Taipei Hsien, Taiwan, R. O. C.
 TEL:886-2-86867781~4 FAX:886-2-86867780
 http://www.richbay.com.tw

DRAWN BY	UNIT	UNIT QTY	SCALE	TOLERANCE	PRODUCT NO.	R-302G2 (00) XX	REV
	mm	1	1:1	X.XX±0.1 XX.XX±0.2 XXX.XX±0.3			
APPROVED BY	RD	APPROVED BY	RD	ID NO	INTERIM NO.	NEW NO.	D
	113.10.11 吳勝霖		113.10.11 張育誠	241011A23			