



* Images may differ from the real thing.

SFTL-6P-24V-3A3B

Number of poles: 6

Applicable Relay : SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B

Terminal Type : Screwless

Stripping length : 8 ~ 10 mm

Material: CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL

Add products of interest

[Find a Distributor](#)

[Compare](#)

[View model specs](#)

Data Sheet

Pole water	6
Relay	SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B
Rated voltage	24VDC±10% ⁻⁻⁻
Rated Load Voltage	250 VAC~ 50/60 Hz, 30 VDC ⁻⁻⁻
Continuous Currents	6A
Light	Action Indicator: Green
Terminal Type	Screwless
Stripping length of wire stripping	8 ~ 10 mm

Insulation Resistance	$\geq 1,000 \text{ M}\Omega$ (500VDC megger)---
Withstand Voltage_Between Coil to Contact	4,000 VAC~ 50/60 Hz for 1 minute
Withstand voltage_between two pole contacts	2,500 VAC~ 50/60 Hz for 1 minute
Withstand voltage_to-copper contact	2,500 VAC~ 50/60 Hz for 1 minute
Vibration resistant	10 ~ 55 Hz Double Amplitude 0.75 mm X, Y, Z direction 2 hours each
Shock	300 m/s ² ($\approx 30 \text{ G}$) X, Y, Z 3 times each
Ambient temperature	-25 ~ 70 °C, when preserved: -30 ~ 80 °C (no freezing or condensation)
Ambient humidity	25 ~ 85 % RH, when preserved: 25 ~ 85 % RH (no freezing or condensation)
Protective Structure	IP20 (IEC compliant)
material	CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL
Body weight (packaging)	$\approx 51.2 \text{ g}$ ($\approx 99.2 \text{ g}$)

3D Viewer

* 페이지 상단의 제품 이미지 아래 CAD 버튼을 클릭하면 3D Viewer를 확인할 수 있습니다.

홍보자료

홍보 자료는 로그인 없이 다운로드가 가능 합니다.



카탈로그

카탈로그 2023-2...

브로슈어

세이프티 제품군

언어선택

언어선택

다운로드

미리보기

다운로드

미리보기



1



테크니컬 자료

[더보기](#)

전체 7

매뉴얼 2

CAD 2

인증서 3

소프트웨어 0

상세 모델별 3D 도면은 하단 모델페이지에서 확인과 도면 다운로드가 가능합니다.

매뉴얼 > [취급 설명서](#)

언어선택

PDF

SFT Series

매뉴얼 > [제품 매뉴얼](#)

언어선택

PDF

SFT Series

CAD > [2D](#)

ZIP

2D CAD (...)

CAD > [3D](#)

ZIP

3D CAD (...)

인증서 > [UKCA](#)

PDF

SFT Serie...

인증서 > [CE](#)

PDF

SFT Serie...



1

2

