



* Images may differ from the real thing.

SFTL-4P-24V-3A1B

Number of poles: 4

Applicable Relay : SFS2-DC24V: 2A2B, SFS3-DC24V: 3A1B

Terminal Type : Screwless

Stripping length : 8 ~ 10 mm

Material: CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL

Add products of interest

[Find a Distributor](#)

[Compare](#)

[View model specs](#)

Data Sheet

Pole water	4
Relay	SFS2-DC24V: 2A2B, SFS3-DC24V: 3A1B
Rated voltage	24VDC±10% ⁻⁻⁻
Rated Load Voltage	250 VAC~ 50/60 Hz, 30 VDC ⁻⁻⁻
Continuous Currents	6A
Light	Action Indicator: Green
Terminal Type	Screwless
Stripping length of wire stripping	8 ~ 10 mm

Insulation Resistance	$\geq 1,000 \text{ M}\Omega$ (500VDC megger)---
Withstand Voltage_Between Coil to Contact	4,000 VAC~ 50/60 Hz for 1 minute
Withstand voltage_between two pole contacts	2,500 VAC~ 50/60 Hz for 1 minute
Withstand voltage_to-copper contact	2,500 VAC~ 50/60 Hz for 1 minute
Vibration resistant	10 ~ 55 Hz Double Amplitude 0.75 mm X, Y, Z direction 2 hours each
Shock	300 m/s ² ($\approx 30 \text{ G}$) X, Y, Z 3 times each
Ambient temperature	-25 ~ 70 °C, when preserved: -30 ~ 80 °C (no freezing or condensation)
Ambient humidity	25 ~ 85 % RH, when preserved: 25 ~ 85 % RH (no freezing or condensation)
Protective Structure	IP20 (IEC compliant)
material	CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL
Body weight (packaging)	$\approx 39.8 \text{ g}$ ($\approx 88 \text{ g}$)

3D Viewer

* Click the CAD button below the product image at the top of the page to check out the 3D Viewer.

Flyer

Promotional materials can be downloaded without logging in.



[catalog](#)
Catalogs 2023-...



[Brochure](#)
Safety range

View in original I...

View in original I...

download Snippets

download Snippets



Technical Resources

[More](#)

whole 7

manual 2

CAD 2

certificate 3

software 0

Detailed model-specific 3D drawings can be viewed and downloaded on the model page below.

manual >
[Instruction manual](#)
 PDF **SFT Series**

View in ori...

manual >
[Product Manuals](#)
 PDF **SFT Series**

View in ori...

