



\* Images may differ from the real thing.

# SFTL-6P-24V-5A1B

Number of poles: 6

Applicable Relay : SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B

Terminal Type : Screwless

Stripping length : 8 ~ 10 mm

Material: CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL

Add products of interest

[Find a Distributor](#)

[Compare](#)

[View model specs](#)

## Data Sheet

|                                    |  |
|------------------------------------|--|
| Pole water                         | 6  |
| Relay                              | SFS4-DC24V: 4A2B, SFS5-DC24V: 5A1B, SFS6-DC24V: 3A3B |
| Rated voltage                      | 24VDC±10% <sup>---</sup>                             |
| Rated Load Voltage                 | 250 VAC~ 50/60 Hz, 30 VDC <sup>---</sup>             |
| Continuous Currents                | 6A   |
| Light                              | Action Indicator: Green                              |
| Terminal Type                      | Screwless  |
| Stripping length of wire stripping | 8 ~ 10 mm  |

|   |  |
|---|--|
| Insulation Resistance                       | $\geq 1,000 \text{ M}\Omega$ (500VDC megger)---                          |
| Withstand Voltage_Between Coil to Contact   | 4,000 VAC~ 50/60 Hz for 1 minute   |
| Withstand voltage_between two pole contacts | 2,500 VAC~ 50/60 Hz for 1 minute   |
| Withstand voltage_to-copper contact         | 2,500 VAC~ 50/60 Hz for 1 minute   |
| Vibration resistant                         | 10 ~ 55 Hz Double Amplitude 0.75 mm X, Y, Z direction 2 hours each       |
| Shock                                       | 300 m/s <sup>2</sup> ( $\approx 30 \text{ G}$ ) X, Y, Z 3 times each     |
| Ambient temperature                         | -25 ~ 70 °C, when preserved: -30 ~ 80 °C (no freezing or condensation)   |
| Ambient humidity                            | 25 ~ 85 % RH, when preserved: 25 ~ 85 % RH (no freezing or condensation) |
| Protective Structure                        | IP20 (IEC compliant)   |
| material                                    | CASE, BASE: PC Terminal: PA66, COPPER, STAINLESS STEEL                   |
| Body weight (packaging)                     | $\approx 51.2 \text{ g}$ ( $\approx 99.2 \text{ g}$ )                    |

## 3D Viewer

\* 페이지 상단의 제품 이미지 아래 CAD 버튼을 클릭하면 3D Viewer를 확인할 수 있습니다.



## Flyer

Promotional materials can be downloaded without logging in.



**catalog**  
Catalogs 2023-...

**Brochure**  
Safety range



download Snippets

download Snippets



# Technical Resources

[More](#)

whole 7

manual 2

CAD 2

certificate 3

software 0

Detailed model-specific 3D drawings can be viewed and downloaded on the model page below.

manual >  
[Instruction manual](#)

View in ori...

PDF **SFT Series**

manual >  
[Product Manuals](#)

View in ori...

PDF **SFT Series**

